

# L17T+



- 17" TN TFT-LCD
- Contrast ratio 700:1
- Luminance 300 cd/m<sup>2</sup>
- 8 ms Response Time
- Integrated TV Tuner



## The 2-in-1 solution

HYUNDAI L17T+ uncompromisingly unites the functional character of a high-end-monitor with that of a television set. Thanks to a response time of 8 ms the device is extremely suitable to the presentation of quickly moving pictures. The computer is joint via the analog D-Sub connection as usual. Other multimedial connections like S-video and Composite enable the connection of many multimedial terminals: DVD Player, game console, digital camera, etc. The integrated TV tuner is comfortably controlled via the provided IR-remote control. The modern design in black-color edition complete the outstanding price-performance ratio of this multifunctional talent.

**HYUNDAI**

# Technical Specifications

# L17T+



<b>Technology</b>	<b>LCD</b>	A-Si TN TFT Active Matrix
<b>Panel Specifications</b>	<b>size / diagonale</b>	17" / 43,18 cm
	<b>viewing angle (horizontal / vertical)</b>	170° / 160°
	<b>pixel pitch</b>	0,264 mm (H x V)
	<b>contrast ratio</b>	700:1 (typical)
	<b>response time</b>	8 ms (typical)
	<b>luminance</b>	300 cd/m <sup>2</sup> (typical)
	<b>aspect ratio</b>	5:4
	<b>active display size</b>	337.92 x 270.336 mm
	<b>colors</b>	16,2 Mio.
<b>Scanning Frequency</b>	<b>horizontal</b>	30 ~ 80 kHz
	<b>vertical</b>	56 ~ 75 Hz
<b>Resolution</b>	<b>maximal</b>	1280 x 1024 @ 75 Hz
	<b>recommended</b>	1280 x 1024 @ 60 Hz
	<b>preset/analog</b>	720 x 400 @ 70 Hz, 640 x 480 @ 60/75 Hz, 800 x 600 @ 56/60/72/75 Hz 1024 x 768 @ 60/70/75 Hz, 1280 x 1024 @ 60/75 Hz
<b>Input Signal</b>	<b>video</b>	RGB analog, Composite Video
	<b>synchronization</b>	H/V separat, Composite Video, S-Video, RF (Tuner)
<b>Connectors</b>	<b>analog</b>	D-Sub 15-pol, S-Video, RCA Composite, TV-Antena
	<b>cable length</b>	1,5 m
<b>Plug-and-Play</b>		VESA DDC 1/2B
<b>User Controls</b>	<b>analog</b>	Contrast, H/V Position, Clock, Auto Adjust, Color Control, Miscellaneous, Input Select, Language Select, Audio
<b>(On-Screen-Menue)</b>		
<b>Lifespan (MTBF)</b>	<b>panel/backlight</b>	50.000 operating hours
<b>Power Management</b>		VESA DPMS
<b>Power Supply System</b>	<b>voltage</b>	110 ~ 240 V AC
	<b>consumption</b>	40W (max.)
<b>Power Supply</b>		external
<b>Low Radiation</b>		TCO 99
<b>Pixel Default Class</b>	<b>ISO 13406-2</b>	Class 2
<b>Safety &amp; Regulations</b>		cTUVus, TUV-GS, CB, FCC, CE, VCCI, JAPAN-S
<b>Other Features</b>	<b>audio system</b>	2 x 2 Watt, Headphone set
	<b>built-in TV tuner</b>	PAL/SECAM
	<b>remote control</b>	inklusiv
	<b>Kensington Security Slot</b>	yes (monitor backside)
	<b>compatible for Wallmount/</b>	VESA Standard (75 x 75 mm)
	<b>swivel arm</b>	
<b>Stand</b>	<b>downtilt</b>	90° / 90°
<b>Cabinet Color</b>		black
<b>Dimensions (W x H x D)</b>	<b>unit</b>	372 x 395 x 185 mm
	<b>packed</b>	438 x 486 x 160 mm
<b>Weight</b>	<b>unit</b>	4.5 kg
	<b>packed</b>	4.9 kg
<b>Guarantee</b>	<b>Pick-up &amp; Return</b>	36 Month
<b>Scope of Delivery</b>		Power cable, D-Sub cable, audio cable, remote control, batteries, installation quick-guide, CD-ROM: user manual, driver, ICM profil

Technical details are subject to change without further notice. Errors excepted. Version: as of August 2006.